

TITAN SLICK SILVER | TSSX-90

High tack chrome silver print vinyl with micro channel liner developed to create eyecatching graphics on powervehicles. Remove the clear polyester protection film before printing.

FACE FILM

Polymeric PVC, chrome silver

Thickness (µm) 90

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	30	
Adhesion to steel	FINAT FTM 1	
20 minutes (180°) N/25mm	25	
24 hours (180°) N/25mm	30	

RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm) 140

PROTECTION FILM

Thickness (µm) 25

PRODUCT APPLICATION

Application temperature (°C)	10 to 25
Service temperature (°C)	-20 to 80

DURABILITY

Outdoor durability (years) 5 Northern-EU climate, vertical exposure

ROLL SIZES

PRINTING METHOD

1370mm x 50m (Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.